

SPECIFICATIONS

ENGINE

Type	1.6 DOHC (unleaded)	2.0 CVVT (unleaded)	2.0 Diesel (unleaded)
Displacement (cc)	1599	1975	1991
Bore x Stroke (mm)	76.5 x 87.0	82.0 x 93.5	83.0 x 92.0
Compression ratio	10.1	10.1	17.7
Max. Power (kW / rpm)	77.2 / 5800	105 / 6000	82.5 / 4000
Max. Torque (Nm / rpm)	143 / 4500	186 / 4500	235 / 1800

- On leaded fuel engines, power & torque figures vary in accordance with local fuel and climate characteristics.
- Please ask your dealer for available engines.

DRIVE TRAIN

Type		Manual			Automatic	
Engine		1.6 DOHC	2.0 CVVT	2.0 Diesel	1.6 DOHC	2.0 CVVT
		5-Speed Transaxle with Floor Shift			4-Speed Transaxle with Floor Shift	
Gear Ratio	1st	3.615	←	3.455	2.846	2.842
	2nd	2.053	←	1.952	1.581	1.529
	3rd	1.393	←	1.296	1.000	←
	4th	1.061	←	0.943	0.685	0.712
	5th	0.837	←	0.698	-	←
	Reverse	3.250	←	3.455	2.176	2.480
Final Gear Ratio		4.056	3.650	3.611	4.041	3.770
Lubricant Oil Capacity (ℓ)		2.150	←	2.1	6.1	7.8

SUSPENSION

Front	Independent MacPherson strut with coil spring, anti-roll stabilizer
Rear	Dual-link type with coil springs, anti-roll stabilizer
Shock absorber	Telescopic hydraulic double acting type

STEERING WHEEL

	4-spoke steering wheel with airbag Energy absorbing collapsible steering column with optional tilt steering
--	--

BRAKES

Front	14-inch ventilated disc, floating - caliper brakes with pads wear warning device
Rear	W / O ABS : 8-inch self adjusting, leading trailing shoe drum brakes with parking brake mechanism W / ABS : 14-inch solid disc, floating - caliper brake with parking brake mechanism

- Some of the equipment illustrated or described in this catalogue may not be supplied as standard equipment and may be available at extra cost.
- Hyundai Motor Co. reserves the right to change specifications and equipment without prior notice.
- The color plates shown may vary slightly from the actual colors due to the limitations of the printing process.
- Please consult your dealer for full information and availability on colors and trim.

DIMENSIONS

